

Seat Belts for Forklift

Forklift Seat Belts - Explained in the Regulation guidelines are the use of seatbelts and operator restraints on lift trucks. It says that the accountability falls on the employers' to make sure that each machinery, piece of equipment and tool is used rightly utilized according to the directions of the producer.

Rough Terrain forklifts have to meet the regulations of ANSI Standard ASME B56.6-1992 with regards to their maintenance, inspection, fabrication, use and design.

Side boom tractors and mobile machine with a Rollover Protective Structure, or ROPS for short, must contain seat belts which meet the requirements of the Society of Automotive Engineers, or SAE, Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whatever mobile equipment includes seat belts required by law, the operator and subsequent passengers should make sure they make use of the belts whenever the vehicle is in motion or engaged in operation because this could cause the machine to become unbalanced and hence, unsafe.

When a seat belt or different operator restraint is needed on a lift truck.

The seat belt requirements while working a forklift depend on various factors. Whether the forklift is outfitted along with a Rollover Protective Structure, the type of forklift itself and the year the forklift was made all contribute to this determination. The manufacturer's directions and the requirements of the applicable standard are referenced in the Regulation.

With regards to to a driver restraint device, enclosure or system, ANSI Standard ASME B56.1-1993 regarding powered industrial trucks, is intended to aid the driver in lessening the possibility of entrapment of the head and/or torso between the truck and the ground in the event of a tip over. The system or restraint device might comprise a seat belt, even if a seat belt is not essentially a part of such machine or system.